

(11) EP 1 475 297 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication: 10.11.2004 Bulletin 2004/46

(51) Int Cl.7: **B62D 51/04**

(21) Application number: 04445056.7

(22) Date of filing: 07.05.2004

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR

HU IE IT LI LU MC NL PL PT RO SE SI SK TR

Designated Extension States:

AL HR LT LV MK

(30) Priority: 08.05.2003 SE 0301345

(71) Applicant: BT INDUSTRIES AB 59581 Mjölby (SE)

(72) Inventors:

- Carlsson, Magnus
 590 74 Vikingstad (SE)
- Wernborg, Sven-Erik
 595 32 Mjölby (SE)
- Svartling, Cecilia
 595 33 Mjölby (SE)
- (74) Representative: Berglund, Erik Wilhelm
 Berglunds Patentbyra AB
 Aspebraten
 590 55 Sturefors (SE)

(54) Safety arrangement at picking truck following a walking person.

(57) Picking truck with a travel platform or the like for the driver, which truck is provided with a sensor for detecting if the driver is on the platform or not and a sensor for the steering angle. The truck allows driving also when the driver does not stand on the platform, but when the driver has stepped down from the platform the maximum permitted travel speed depends on the steering

angle and is reduced in two steps or more or along a graph where the permitted maximum travel speed of the truck is reduced with increasing steering angle. At steering angles over a defined steer angle, for instance 30° and with stepped off driver no travel is permitted.

Description

[0001] This invention is related to picking trucks of the kind that includes a platform or the like for the driver to stand on at the travel of the truck. If the places where the merchandize is to be collected are close to each other this either result in several short walks or little short travels of the truck. In order not to necessitate for the driver to climb onto the truck for these short travels it is known to arrange additional controls on the sides of the truck for the moving straight forward of the truck with reduced speed without the driver climbing up on the truck. For instance the available maximum speed is reduced to half the normally available maximum speed. The reason for this is the security aspect since one does not want the driver run into himself or be jammed by his own truck.

[0002] Even if the above solution makes the use of trucks of this kind more efficient it has the drawback that the truck before you start a series of movements with the driver walking at the side must be adjusted to be comparatively parallel to the store alley so that the driver does not have to climb up on the truck in order to steer it right alternatively to risk that the available walking space at the side of the truck is constantly reduced thereby giving the driver a space for movement that is too narrow for the driver at the picking, with resulting lack of ergonomics for lifting on and off.

[0003] The object of the invention is further to improve the efficiency of picking trucks with a place for the driver to stand. In accordance with the invention this is achieved by the truck in a normal way being provided with sensor means that when the driver leaves his place on the truck initiate a reduction of the maximum available travel speed, for instance half. Different from the known technique steering is still allowed but the maximum travel speed is reduced as a function of the steering movement and when a defined limit angle has been reached no further turning is allowed.

[0004] As an alternative to the above instead or additionally the turning speed of the steering is reduced as a function of the steering angle measured from the center position. Preferably also the maximally possible steering angle is reduced. The risks for the driver can in this way be kept small at the same time as the flexibility gets better.

[0005] Within the concept of the invention both of the above alternatives can be combined with each other so that both the maximal travel speed and the maximum steering angle speed are limited as a function of the steering angle from the center position. In this way only a very slow movement is allowed laterally, which considerably lessens the risk that the driver is jammed or drives over his own feet by mistake.

[0006] The maximum turning speed of the steering movement can be reduced in one step when the driver leaves his place on the truck and/or successively with the steering angle.

[0007] In a preferable further development of the inventive thought only a limited steering angle is allowed to each side, for instance 30° and advantageously available maximum travel speed is reduced to zero at the same angle.

[0008] Within the inventive thought one could also consider letting maximum steering angle speed and value be a function of the travel speed, so that a lower used travel speed allows a larger turn angle speed and/or a larger maximum steering angle. In this way the manouverablility of the truck is increased without compromising the security. By lowering the used speed a larger steering angel can thus be used more or less temporarily for required course correction.

[0009] The reduction of travel speed and/or steering angle speed can be stepwise or along some suitable graph. Advantageously the speed of the truck can be reduced in one step when the driver gets off, for instance halved if the truck a the dismounting had the steering wheel adjusted for movement straight forward and more if steering still takes place at the dismounting.

[0010] At the invention advantageously the same steering means are used when the driver is at the side of the truck as well as when he stands on the truck. By letting the truck retain the low maximum travel speed and/or steering angle speed that is used when maneuvering from the side, even if the driver steps up on the truck, until its drive control has been returned to its zero position, jerks are avoided when the driver steps up on the truck from walking and steering beside it.

[0011] Through the invention the truck becomes both easier to steer and use and more ergonomic at the same time as the security increase.

Claims

- 1. Picking truck with travel platform or the like for the driver, which truck is provided with a sensor for detecting if the driver is on the platform or not, the truck is arranged to allow driving also when the driver has stepped off, **characterized in that** the truck is provided with sensor for the steering angle and so arranged that when the driver has stepped down from the platform the maximum permissible travel speed is reduced stepwise in two or several steps along a graph, where the maximum permissible travel speed of the truck is reduced with a steering angle increasing from a center position corresponding to traveling straight forward.
- 2. Picking truck according to claim 1, characterized in that it is so arranged that the permissible maximum travel speed of the truck with dismounted driver and a steering angle in excess of a defined steering angle, for instance 30° is zero, that is no travel is permitted.

50

3. Picking truck according to any of the preceding claims, characterized in that it is so arranged that the truck continue with unaltered speed if the driver step up on it when it is already in motion and that some additional measure, for instance that the speed control is returned to its zero position, even if very quickly, is required for returning the truck to the normal drive state when the driver is on the platform.

4. Picking truck with a travel platform or the like for the driver, which truck is arranged with a sensor for detecting if the driver is on the platform or not, which truck is arranged to allow driving also when the driver has stepped down, **characterized in that** the truck is provided with sensor for the steering angel and so arranged that when the driver has stepped down from the platform the maximally permitted steering angle speed stepwise or along a graph is reduced as a function of increasing steering angle 20 and/or speed.

5. Picking truck according to claim 4, **characterized** in **that** it is so arranged that when the driver has stepped off and a defined steering angel has been reached, for instance 30° no larger steering angle is permitted.



EUROPEAN SEARCH REPORT

Application Number EP 04 44 5056

`O+0 :	Citation of document with i	ndication, where appropriate,	Relevant	CLASSIFICATION OF THE
Category	of relevant pass		to claim	APPLICATION (Int.C1.7)
4	US 6 094 897 A (VEL 1 August 2000 (2000 * column 17, line 6		1,4	B62D51/04
A	US 4 336 858 A (LOY 29 June 1982 (1982- * column 7, line 32 claims 6,7; figures	06-29) - column 8, line 3;	1	
А	US 4 D36 323 A (SCH 19 July 1977 (1977- * column 5, line 43		1	
A	US 4 386 674 A (SUG 7 June 1983 (1983-0 * claims 1-3,7; fig	6-07)	4	
				TECHNICAL FIELDS SEARCHED (Int.Cl.7)
				B62D B60K
тинентинент турстваний				
	The present search report has	been drawn up for all claims		
<u>.</u>	Place of search	Date of completion of the search		Examiner
	The Hague	24 August 2004	Hag	eman, L
G,	ATEGORY OF CITED DOCUMENTS	T : theory or principle	underlying the	Invention
X : pani Y : pani docu	icularly relevant if taken alone icularly relevant if combined with anot unent of the same category	E : earlier palent doc after the filing date her D : document cited in L : document cited to	cument, but publice the application of the reasons.	ished on, or
O: non	nological background written disclosure mediate document	& : member of the sa document		y, corresponding

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 04 44 5056

This annex lists the patent family members relating to the patent documents cited in the above—mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-08-2004

Patent document cited in search report		Publication date	i	Patent family member(s)		Publication date
 US 6094897	L A	01-08-2000	US	6059055 A		09-05-200
00 0004007	, ,	01 00 5000	US	5809755 A		22-09-199
			US	5600944 A		11-02-199
			ÜŠ	5507138 A	•	16-04-199
			US		1	08-05-200
			US		1	20-02-200
			US		1	11-12-200
			US	2004103629 A		03-06-200
			US	2002014063 A		07-02-200
			US	2002014003 A		08-08-200
			US	2002104708 A		05-12-200
						31-10-200
			U\$	6138446 A		
			US		31	06-02-200
			ПZ		31	21-08-200
			US		31	16-10-200
			US		.1	22-11-200
			US		.1	07-03-200
			US	5984031 A		16-11-199
			US	5964082 A		12-10-199
			US	6085504 A		11-07-200
			US		1	16-01-200
			US	6189305 B		20-02-200
			US	6405515 B		18-06-200
			US	2004055267 A		25-03-200
المراقبة والمراقبة والمراقب والمراقبة والمراقب	حہ میں محمد بہت 1960ء انہے، واقع	tu Taga ayank bilang ayan dariik yann ciriya ajan ciriik bajah biriin Waliy diyar.	US	5765347 A		16-06-199
US 4336858	A	29-06-1982	NONE	منت الكتار برنام منافه الكراء مناف الإنجاع بالمنا المناف الكراء مناف الكتاب المناف الكتاب الكتاب الكتاب الكتاب	الكثبة محمد مداقة تجرب والبدية والأشار أشياط ال	urberen andresse bestigen degree bester bester Upper mannet descen street bester
US 4036323	A	19-07-1977	DE	2403586 A	.1	31-07-197
	• •		DE	2408764 A		04-09-197
			CH	587737 A		13-05-197
			FR	2258973 A		22-08-197
			GB	1488181 A		05-10-197
			IT	1052134 B		20-06-198
US 4386674	Α	07-06-1983	JP	1379272 C		28-05-198
			JP	56095768 A	1	03-08-198
			JP	61047743 B		21-10-198
			AU	521936 B	2	06-05-198
			AU	6557480 A		02-07-198
			BR	8008427 A		14-07-198
			DE	3048856 A	1	17-09-198
			FI	803997 A		28-06-198
			GB	2066538 A	• •	08-07-198
			ĪŢ	1134812 B	•	20-08-198
			NL	8006728 A		16-07-198

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 04 44 5056

This annex lists the patent family members relating to the patent documents cited in the above—mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-08-2004

cited in search report		date	member(s)			date
US 4386674	A		SE SE	448581 8009131	A	02-03-19 28-06-19
محمد القلام بالمحمد القلام المحمد	man, sekah danah penyir Masil bilah dada	g dirin (Signa (Minn Mills) (SASS)- product albiffly reality (SASS) printed (Minn (Minn)		ه دسته ۱۳۰ های ۱۳۰۰ خاک ۱۳۰۰ است خانف سبت کافت دیجت د	ngga nakugi 40004 tinga. Jilaki tuatin 18444	ستنفز بهست نطفه مستف فالده مستاه فلسته فالتها والمناه والمناه والمناه
			•			
more details about this anr						
			······································			